

Product Name: SCP-360 Black Ink

Substrates Marked

Preferred: Various Wood Products **Acceptable:** Porous Substrates

Product Specifications/Characteristics

UN Number	N/A	Flash Point	>212° F (>100°C)
Туре	Ink Jet	Recommended Storage	40°- 90° F (4.4°C – 32.2°C)
Colorant	Dye	Shelf Life	2 years
Viscosity	Liquid	Package	Vapor barrier polyethylene
Drying Time	5-60 seconds	Unit	Various
Open Time	N/A	Density	8.38 lbs/gal
DOT Regulations	N/A	RCRA Waste Number	N/A
VOC	0 g/l	Thinner	N/A
SDS Sheet Number	5861	Cleaner	PX370C
HMIS Rating	1-0-0	NFPA Rating	1-0-0
Carcinogen	No	Specific Gravity	1.006

Description/Special Properties

True Zero VOC and HAPS free black water-based dye ink for use on wood products and various other porous substrates. This ink will show good UV resistance as well as good water fastness after drying. This ink is to be used on porous substrates and sample marking is recommended prior to use. This ink has shown excellent performance in the printheads and requires little maintenance with proper use. This ink has been tested and approved as an APA Trademark Ink.

Application/Compatibility

Printhead: 8000+, Single Valve Head

Limitations: N/A Formulations Available

Item Number	Unit of Measure
71085742	Case of 6 x 1 Liter Bottles
71085740	Swedot Case of 6 x 1 Liter Bottles
71085744	5 Gallon Pail
71085743	55 Gallon Drum
71202911	275 Gallon Tote

A Safety Data Sheet is furnished with every order.

Original Date: June 21, 2016 Revision Date: February 13, 2017

