

Product Name: SCP-340 Black Pigmented Ink

Substrates Marked

Preferred: Engineered Wood Products, Various Wood Products
Acceptable: Porous substrates

Product Specifications/Characteristics

UN Number	N/A	Flash Point	>212° F (>100°C)
Type	Ink Jet	Recommended Storage	40°- 90° F (4.4°C – 32.2°C)
Colorant	Pigment	Shelf Life	1 year
Viscosity	Liquid	Package	Vapor barrier polyethylene
Drying Time	1-5 seconds	Unit	Various
Open Time	N/A	Density	8.59 lbs/gal
DOT Regulations	N/A	RCRA Waste Number	N/A
VOC	92 g/l	Thinner	N/A
SDS Sheet Number	4882	Cleaner	SCP-340C Cleaner
HMS Rating	1-0-0	NFPA Rating	1-0-0
Carcinogen	No	Specific Gravity	1.032

Description/Special Properties

Black water based pigmented ink for use on engineered wood products and various other porous substrates. This ink will show excellent UV resistance as well as good water fastness after drying. This ink is to be used on porous substrates and sample marking is recommended prior to use. This ink has shown excellent performance in the printheads and requires little maintenance with proper use. This ink has been tested and approved as an APA Trademark Ink.

Application/Compatibility

Printhead: 8000+ Maxi
Rubber Compounds: No single valve printheads

Formulations Available

Item Number	Unit of Measure
71078848	Case of 6 x 1 Liter Bottles
71078849	Case of 6 x 1 Liter Bottles
71080439	Case of 4 x 4 Liter Bottles
71080440	Case of 2 x 4 Liter Bottles
71078168	5 Gallon Pail
71078847	55 Gallon Drum

A Safety Data Sheet is furnished with every order.

Original Date: December 5, 2013

Revision Date: March 23, 2017
