

## Product Name: SCP-799A Black (FD) Ink

---

### Substrates Marked

**Preferred:** Various porous and non-porous substrates  
**Acceptable:** N/A

### Product Specifications/Characteristics

<b>UN Number</b>	1210	<b>Flash Point</b>	16° F (-9°C)
<b>Type</b>	Ink Jet	<b>Recommended Storage</b>	32°- 90° F (0°C – 32.2°C)
<b>Colorant</b>	Dye	<b>Shelf Life</b>	2 years
<b>Viscosity</b>	Liquid	<b>Package</b>	Vapor barrier polyethylene
<b>Drying Time</b>	5-10 seconds	<b>Unit</b>	Various
<b>Open Time</b>	N/A	<b>Density</b>	6.96 lbs/gal
<b>DOT Regulations</b>	Flammable	<b>RCRA Waste Number</b>	D001, D035, F005
<b>VOC</b>	784 g/l	<b>Thinner</b>	N/A
<b>SDS Sheet Number</b>	4837	<b>Cleaner</b>	SCP-700C Cleaner
<b>HMIS Rating</b>	2*-3-0	<b>NFPA Rating</b>	2-3-0
<b>Carcinogen</b>	No	<b>Specific Gravity</b>	0.836

### Description/Special Properties

Slower drying version of SCP-700A Black Ink for use on both porous and non-porous applications. Dry times for this ink will be 5-10 seconds. This ink will have good UV resistance and adhesion to a wide variety of substrates. Conforms to A-A-208 for performance on substrate (Reference sections 5.4 & 5.5).

### Application/Compatibility

**Printhead:** 8000+  
**Rubber Compounds:** N/A

### Formulations Available

Item Number	Unit of Measure
71064821	Case of 6 x 1 Liter Bottles
71078460	5 Gallon Pail

A Safety Data Sheet is furnished with every order.

**Original Date:** March 7, 2018

**Revision Date:**

---