

Product Name: SCP-730 Black Pigmented (FD) Ink

Substrates Marked

Preferred: Various non-porous substrates
Acceptable: N/A

Product Specifications/Characteristics

UN Number	1210	Flash Point	16° F (-9°C)
Type	Ink Jet	Recommended Storage	32°- 90° F (0°C – 32.2°C)
Colorant	Pigment	Shelf Life	1 year
Viscosity	Liquid	Package	Vapor barrier polyethylene
Drying Time	1-5 seconds	Unit	Various
Open Time	N/A	Density	6.89 lbs/gal
DOT Regulations	Flammable	RCRA Waste Number	D001, D035, F005
VOC	777 g/l	Thinner	N/A
SDS Sheet Number	5019	Cleaner	SCP-700C Cleaner
HMS Rating	1-3-0	NFPA Rating	1-3-0
Carcinogen	No	Specific Gravity	0.827

Description/Special Properties

Fast dry pigmented ink for use on non-porous applications where increased UV and weathering resistance is needed. UV resistance on most non-porous substrates will exceed 1 year. Dry times for this ink will be 1-5 seconds. Conforms to A-A-208 for performance on substrates (Reference sections 5.4 & 5.5).

Application/Compatibility

Printhead: 8000+
Rubber Compounds: N/A

Formulations Available

Item Number	Unit of Measure
71002379	Case of 6 x 1 Liter Bottles
71002380	Case of 6 x 1 Liter Bottles
71078968	Case of 2 x 4 Liter Bottles
71002377	5 Gallon Pail
71002376	55 Gallon Drum

A Safety Data Sheet is furnished with every order.

Original Date: December 30, 2012
Revision Date: March 23, 2017
