

## Product Name: SCP-719 Special Red (FD) Ink

---

### Substrates Marked

**Preferred:** Various porous and non-porous substrates  
**Acceptable:** N/A

### Product Specifications/Characteristics

<b>UN Number</b>	1210	<b>Flash Point</b>	16° F (-9°C)
<b>Type</b>	Ink Jet	<b>Recommended Storage</b>	32°- 90° F (0°C – 32.2°C)
<b>Colorant</b>	Dye	<b>Shelf Life</b>	2 years
<b>Viscosity</b>	Liquid	<b>Package</b>	Vapor barrier polyethylene
<b>Drying Time</b>	1-5 seconds	<b>Unit</b>	Various
<b>Open Time</b>	N/A	<b>Density</b>	7.14 lbs/gal
<b>DOT Regulations</b>	Flammable	<b>RCRA Waste Number</b>	D001, D035, F005
<b>VOC</b>	758 g/l	<b>Thinner</b>	N/A
<b>SDS Sheet Number</b>	4832	<b>Cleaner</b>	SCP-700C Cleaner
<b>HMS Rating</b>	2*-3-0	<b>NFPA Rating</b>	2-3-0
<b>Carcinogen</b>	No	<b>Specific Gravity</b>	0.857

### Description/Special Properties

Fast dry ink for use on both porous and non-porous applications. Dry times for this ink will be 1-5 seconds. This ink will have good UV resistance and adhesion to a wide variety of substrates. Dry times for this ink can be speeded up with air or heated air. This ink is a bright, brilliant fluorescent red color that will provide a bold high contrast mark. It has been used in some applications using optical vision systems. All applications should be tested for proper functionality.

### Application/Compatibility

**Printhead:** 8000+  
**Rubber Compounds:** N/A

### Formulations Available

Item Number	Unit of Measure
71002256	Case of 6 x 1 Liter Bottles
71002254	5 Gallon Pail

A Safety Data Sheet is furnished with every order.

**Original Date:** November 11, 2012  
**Revision Date:** June 28, 2016

---