

Product Name: L-268 Yellow Pigmented Ink

Substrates Marked

Preferred: PVC, Polypropylene, Rubber, Wood, Metals
Acceptable: Various non-porous substrates

Product Specifications/Characteristics

UN Number	1210	Flash Point	16° F (-9°C)
Type	CIJ	Recommended Storage	32°- 90° F (0°C – 32.2°C)
Colorant	Pigment	Shelf Life	1 year
Viscosity	Liquid	Package	Vapor barrier polyethylene
Drying Time	1-5 seconds	Unit	½ Liter Bottle
Open Time	N/A	Density	N/A
DOT Regulations	Flammable	RCRA Waste Number	D001, D035, F005
VOC	N/A	Thinner	L-9219 Make-up Solution
SDS Sheet Number	5763	Cleaner	L-200
HMIS Rating	1-3-0	NFPA Rating	1-3-0
Carcinogen	No	Specific Gravity	N/A

Description/Special Properties

Opaque yellow ink designed for use on black and dark colored substrates. This ink has good all-around properties and fast drying time. Good light fastness, resistant to migration and transfer and good solvent resistant. Recommended application could include cables, pipes, tubing, electrical components, rubber moldings and extrusions. This ink is NOT recommended for use with glass or PTFE. Pigmented CIJ inks will require more maintenance in general and especially at higher operating temperatures.

Application/Compatibility

Printhead: C84
Rubber Compounds: N/A

Formulations Available

Item Number	Unit of Measure
71002625	Case of 6 x ½ Liter Bottles

A Safety Data Sheet is furnished with every order.

Original Date: November 26, 2012

Revision Date: March 23, 2017
