

Product Name: L-1080R White Pigmented Ink

Substrates Marked

Preferred: PVC, Polypropylene, Polycarbonate, Metals
Acceptable: Other non-porous substrates

Product Specifications/Characteristics

UN Number	1210	Flash Point	16° F (-9°C)
Type	CIJ	Recommended Storage	40°- 90° F (4.4°C – 32.2°C)
Colorant	Pigment	Shelf Life	1 year
Viscosity	Liquid	Package	Vapor barrier polyethylene
Drying Time	1-5 seconds	Unit	½ Liter Bottle
Open Time	N/A	Density	8.34 lbs/gal
DOT Regulations	Flammable	RCRA Waste Number	D001, D035, F005
VOC	709 g/l	Thinner	L-9219 Make-up Solution
SDS Sheet Number	5492	Cleaner	L-200
HMIS Rating	1*-3-0	NFPA Rating	1-3-0
Carcinogen	No	Specific Gravity	1.001

Description/Special Properties

Opaque white ink designed for use on black and dark colored substrates. This ink has good all-around properties and fast drying time. Good light fastness, weather resistance and resistance to migration and transfer. Recommended application could include cables, pipes, tubing, electrical components, rubber moldings and extrusions. This ink is not recommended for use with glass or PTFE.

Application/Compatibility

Printhead: C84
Rubber Compounds: N/A

Formulations Available

Item Number	Unit of Measure
71002870	Case of 6 x ½ Liter Bottles

A Safety Data Sheet is furnished with every order.

Original Date: November 26, 2012

Revision Date: March 23, 2017
