

Product Name: SCP-101 Black Ink

Substrates Marked

Preferred: Corrugated board and paper

Acceptable: Porous substrates

Product Specifications/Characteristics

1 Todate operations, original actorisation			
UN Number	1210	Flash Point	73° F (23°C)
Туре	Ink Jet	Recommended Storage	40°- 90° F (4.4°C – 32.2°C)
Colorant	Dye	Shelf Life	2 years
Viscosity	Liquid	Package	Vapor barrier polyethylene
Drying Time	1-5 seconds	Unit	Various
Open Time	N/A	Density	7.32 lbs/gal
DOT Regulations	Flammable	RCRA Waste Number	D001
VOC	802 g/l	Thinner	N/A
SDS Sheet Number	4842	Cleaner	SCP-100C Cleaner
HMIS Rating	2-3-0	NFPA Rating	1-3-0
Carcinogen	No	Specific Gravity	0.867

Description/Special Properties

Ink for porous surfaces. Dry times for this ink will depend on the porosity of the substrate. It must be used on porous surfaces. This is the standard corrugated black marking ink. This material is approved for FDA 21 CFR 170.39.

Application/Compatibility

Printhead: 8000+

Rubber Compounds: Buna-N, EPT, Viton

Formulations Available

Item Number	Unit of Measure
71229009	Case of 6 x 1 Liter Bottles
71228926	Case of 2 x 4 Liter Bottles
71229008	5 Gallon Pail
71229010	55 Gallon Drum

A Safety Data Sheet is furnished with every order.

Original Date: August 8, 2022

Revision Date:

