

## Product Name: JAM-3002 Green (WB) Ink

---

### Substrates Marked

**Preferred:** Corrugated board and paper  
**Acceptable:** Porous substrates

### Product Specifications/Characteristics

<b>UN Number</b>	N/A	<b>Flash Point</b>	>212° F (>100°C)
<b>Type</b>	Ink Jet	<b>Recommended Storage</b>	40°- 90° F (4.4°C – 32.2°C)
<b>Colorant</b>	Dye	<b>Shelf Life</b>	2 years
<b>Viscosity</b>	Liquid	<b>Package</b>	Vapor barrier polyethylene
<b>Drying Time</b>	1-5 seconds	<b>Unit</b>	Various
<b>Open Time</b>	N/A	<b>Density</b>	8.47 lbs/gal
<b>DOT Regulations</b>	N/A	<b>RCRA Waste Number</b>	N/A
<b>VOC</b>	0 g/l	<b>Thinner</b>	N/A
<b>SDS Sheet Number</b>	5405	<b>Cleaner</b>	JAM-3005 Cleaner
<b>HMIS Rating</b>	1*-0-0	<b>NFPA Rating</b>	1-0-0
<b>Carcinogen</b>	No	<b>Specific Gravity</b>	1.016

### Description/Special Properties

Water based JAM ink for porous surfaces. Dry times for this ink will depend on the porosity of the substrate. It must be used on porous surfaces. Will not ignite or support combustion. This ink has zero VOC's.

### Application/Compatibility

**Printhead:** 8000+  
**Rubber Compounds:** Buna-N, EPT, Viton

### Formulations Available

Item Number	Unit of Measure
71000963	Case of 6 x 1 Liter Bottles
71000957	Case of 4 x 4 Liter Bottles
71000958	Case of 2 x 4 Liter Bottles
71000961	5 Gallon Pail
71000959	55 Gallon Drum
71000960	55 Gallon Drum

A Safety Data Sheet is furnished with every order.

**Original Date:** June 24, 2016  
**Revision Date:**

---