

# Product Name: DPI-352 Green Ink

## Substrates Marked

Preferred:	Corrugated Board, Paper
Acceptable:	Other Porous Substrates

### **Product Specifications/Characteristics**

UN Number	N/A	Flash Point	>212° F (>100°C)
Туре	Ink Jet	Recommended Storage	40°-90° F (4.4°C – 32.2°C)
Colorant	Dye	Shelf Life	2 years
Viscosity	Liquid	Package	Steel
Drying Time	5-60 seconds	Unit	Various
Open Time	N/A	Density	8.47 lbs/gal
DOT Regulations	N/A	RCRA Waste Number	N/A
VOC	0 g/l	Thinner	N/A
SDS Sheet Number	5470	Cleaner	PX370C
HMIS Rating	1*-0-0	NFPA Rating	1-0-0
Carcinogen	No	Specific Gravity	1.016

### **Description/Special Properties**

Water based ink for use in packaging applications on porous surfaces. This ink produces a dark green mark and has excellent drop formation on most porous surfaces. Dry times for this ink will depend on the porosity of the substrate. It must be used on porous surfaces. This ink can be used in all printheads.

#### Application/Compatibility

**Printhead:** 8000+ printheads – proper conditioning and calibration required **Rubber Compounds:** N/A

#### **Formulations Available**

Item Number	Unit of Measure	
71002261	5 Gallon Pail	

A Safety Data Sheet is furnished with every order.

Original Date: June 22, 2016 Revision Date: March 23, 2017

