

Product Name: JAM-2004 DW Black (SB) Ink

Substrates Marked

Preferred: Drywall and Gypsum Board
Acceptable: Porous substrates

Product Specifications/Characteristics

UN Number	1210	Flash Point	24.8° F (-4°C)
Type	Ink Jet	Recommended Storage	40°- 90° F (4.4°C – 32.2°C)
Colorant	Dye	Shelf Life	2 years
Viscosity	Liquid	Package	Vapor barrier polyethylene
Drying Time	30-40 seconds	Unit	Various
Open Time	N/A	Density	6.71 lbs/gal
DOT Regulations	Flammable	RCRA Waste Number	D001
VOC	795 g/l	Thinner	N/A
SDS Sheet Number	5214	Cleaner	JAM-2005 Cleaner
HMIS Rating	2*-3-0	NFPA Rating	2-3-0
Carcinogen	No	Specific Gravity	0.806

Description/Special Properties

JAM ink for drywall or gypsum board. Very pale color of the inks allows latex paint to be applied over the mark without the ink showing through. The color and resin content are too low for use as a non-porous ink.

Application/Compatibility

Printhead: 8000+
Rubber Compounds: Buna-N, EPT, Viton

Formulations Available

Item Number	Unit of Measure
71000713	Case of 4 x 4 Liter Bottles
71000714	Case of 2 x 4 Liter Bottles
71002805	5 Gallon Pail
71000716	55 Gallon Drum

A Safety Data Sheet is furnished with every order.

Original Date: June 24, 2016
Revision Date:
