

## Product Name: JAM-2030 DW Green (SB) Ink

---

### Substrates Marked

**Preferred:** Drywall and Gypsum Board  
**Acceptable:** N/A

### Product Specifications/Characteristics

<b>UN Number</b>	1210	<b>Flash Point</b>	24.8° F (-4°C)
<b>Type</b>	Ink Jet	<b>Recommended Storage</b>	40°- 90° F (4.4°C – 32.2°C)
<b>Colorant</b>	Dye	<b>Shelf Life</b>	2 years
<b>Viscosity</b>	Liquid	<b>Package</b>	Vapor barrier polyethylene
<b>Drying Time</b>	1-5 seconds	<b>Unit</b>	Various
<b>Open Time</b>	N/A	<b>Density</b>	6.71 lbs/gal
<b>DOT Regulations</b>	Flammable	<b>RCRA Waste Number</b>	D001
<b>VOC</b>	793 g/l	<b>Thinner</b>	N/A
<b>SDS Sheet Number</b>	5301	<b>Cleaner</b>	JAM-2005 Cleaner
<b>HMIS Rating</b>	2*-3-0	<b>NFPA Rating</b>	2-3-0
<b>Carcinogen</b>	No	<b>Specific Gravity</b>	0.805

### Description/Special Properties

JAM ink for drywall or gypsum board. Very pale color of the inks allows latex paint to be applied over the mark without the ink showing through. The color and resin content are too low for use as a non-porous ink.

### Application/Compatibility

**Printhead:** 8000+  
**Rubber Compounds:** Buna-N, EPT, Viton

### Formulations Available

Item Number	Unit of Measure
71000797	5 Gallon Pail
71000796	55 Gallon Drum

A Safety Data Sheet is furnished with every order.

**Original Date:** March 17, 2013  
**Revision Date:** June 24, 2016

---