

Product Name: JAM-3001 Blue (WB) Ink

Substrates Marked

Preferred: Corrugated board and paper
Acceptable: Porous substrates

Product Specifications/Characteristics

| | | | |
|-------------------------|-------------|----------------------------|-----------------------------|
| UN Number | N/A | Flash Point | >212° F (>100°C) |
| Type | Ink Jet | Recommended Storage | 40°- 90° F (4.4°C – 32.2°C) |
| Colorant | Dye | Shelf Life | 2 years |
| Viscosity | Liquid | Package | Vapor barrier polyethylene |
| Drying Time | 1-5 seconds | Unit | Various |
| Open Time | N/A | Density | 8.44 lbs/gal |
| DOT Regulations | N/A | RCRA Waste Number | N/A |
| VOC | 0 g/l | Thinner | N/A |
| SDS Sheet Number | 5404 | Cleaner | JAM-3005 Cleaner |
| HMIS Rating | 1*-0-0 | NFPA Rating | 1-0-0 |
| Carcinogen | No | Specific Gravity | 1.013 |

Description/Special Properties

Water based JAM ink for porous surfaces. Dry times for this ink will depend on the porosity of the substrate. It must be used on porous surfaces. Will not ignite or support combustion. This ink has zero VOC's.

Application/Compatibility

Printhead: 8000+
Rubber Compounds: Buna-N, EPT, Viton

Formulations Available

| Item Number | Unit of Measure |
|--------------------|-----------------------------|
| 71000955 | Case of 6 x 1 Liter Bottles |
| 71000950 | Case of 4 x 4 Liter Bottles |
| 71000951 | Case of 2 x 4 Liter Bottles |
| 71000953 | 5 Gallon Pail |
| 71000952 | 55 Gallon Drum |

A Safety Data Sheet is furnished with every order.

Original Date: March 17, 2013
Revision Date: June 24, 2016
