

Product Name: JAM-3012 Brown (WB) Ink

Substrates Marked

Preferred: Corrugated board and paper
Acceptable: Porous substrates

Product Specifications/Characteristics

UN Number	N/A	Flash Point	>212° F (>100°C)
Type	Ink Jet	Recommended Storage	40°- 90° F (4.4°C – 32.2°C)
Colorant	Dye	Shelf Life	2 years
Viscosity	Liquid	Package	Vapor barrier polyethylene
Drying Time	1-5 seconds	Unit	Various
Open Time	N/A	Density	8.40 lbs/gal
DOT Regulations	N/A	RCRA Waste Number	N/A
VOC	0 g/l	Thinner	N/A
SDS Sheet Number	4899	Cleaner	JAM-3005 Cleaner
HMIS Rating	1*-0-0	NFPA Rating	1-0-0
Carcinogen	No	Specific Gravity	1.009

Description/Special Properties

Water based JAM ink for porous surfaces. Dry times for this ink will depend on the porosity of the substrate. It must be used on porous surfaces. Will not ignite or support combustion. This ink has zero VOC's.

Application/Compatibility

Printhead: 8000+
Rubber Compounds: Buna-N, EPT, Viton

Formulations Available

Item Number	Unit of Measure
71000988	Case of 4 x 4 Liter Bottles

A Safety Data Sheet is furnished with every order.

Original Date: March 17, 2013

Revision Date: June 24, 2016
