

## Product Name: JAM-3013 SCT Blue (WB) Ink

---

### Substrates Marked

**Preferred:** Corrugated board and paper  
**Acceptable:** Porous substrates

### Product Specifications/Characteristics

<b>UN Number</b>	N/A	<b>Flash Point</b>	>212° F (>100°C)
<b>Type</b>	Ink Jet	<b>Recommended Storage</b>	40°- 90° F (4.4°C – 32.2°C)
<b>Colorant</b>	Dye	<b>Shelf Life</b>	2 years
<b>Viscosity</b>	Liquid	<b>Package</b>	Vapor barrier polyethylene
<b>Drying Time</b>	1-5 seconds	<b>Unit</b>	Various
<b>Open Time</b>	N/A	<b>Density</b>	8.43 lbs/gal
<b>DOT Regulations</b>	N/A	<b>RCRA Waste Number</b>	N/A
<b>VOC</b>	0 g/l	<b>Thinner</b>	N/A
<b>SDS Sheet Number</b>	5423	<b>Cleaner</b>	JAM-3005 Cleaner
<b>HMIS Rating</b>	1*-0-0	<b>NFPA Rating</b>	1-0-0
<b>Carcinogen</b>	No	<b>Specific Gravity</b>	1.012

### Description/Special Properties

Water based JAM ink for porous surfaces. Dry times for this ink will depend on the porosity of the substrate. It must be used on porous surfaces. Will not ignite or support combustion. This ink has zero VOC's.

### Application/Compatibility

**Printhead:** 8000+  
**Rubber Compounds:** Buna-N, EPT, Viton

### Formulations Available

Item Number	Unit of Measure
71000989	Case of 4 x 4 Liter Bottles
71000990	Case of 2 x 4 Liter Bottles
71000991	5 Gallon Pail

A Safety Data Sheet is furnished with every order.

**Original Date:** June 24, 2016  
**Revision Date:**

---