



SAFETY DATA SHEET JAM3500 (WB) Cleaner

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name JAM3500 (WB) Cleaner
Product number 71001680,71001681
Container size 6 x 1 Liter,6 x 1 Liter

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Ink cleaner for printing inks.
Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Matthews Marking Systems
6515 Penn Avenue
Pittsburgh, PA 15206
412.665.2500
412.828.4545
info@matw.com

Manufacturer Matthews Marking Systems
101 Fairview Ave.
Pittsburgh, PA 15238

1.4. Emergency telephone number

Emergency telephone Chemtrec US : 1-800-424-9300 Chemtrec World: 1-703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified
Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318
Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) Xi; R41, R38

2.2. Label elements

Pictogram



Signal word Danger
Hazard statements H315 Causes skin irritation.
H318 Causes serious eye damage.

JAM3500 (WB) Cleaner

Comments	Full list of Hazard Statements is found in Sec. 16
Precautionary statements	<p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P280 Wear protective gloves/protective clothing/eye protection/face protection.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P332+P313 If skin irritation occurs: Get medical advice/attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p>
Contains	Isopropanol, Ammonium hydroxide
Supplementary precautionary statements	<p>P310 Immediately call a POISON CENTER/doctor.</p> <p>P321 Specific treatment (see medical advice on this label).</p>

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Isopropanol	10-30%
CAS number: 67-63-0	EC number: 200-661-7
Classification	Classification (67/548/EEC or 1999/45/EC)
Flam. Liq. 2 - H225	F; R11. Xi; R36. R67
Eye Irrit. 2 - H319	
STOT SE 3 - H336	
Ammonium hydroxide	1-5%
CAS number: 1336-21-6	EC number: 215-647-6
M factor (Acute) = 1	
Classification	Classification (67/548/EEC or 1999/45/EC)
Acute Tox. 4 - H302	C; R34. N; R50
Skin Corr. 1B - H314	
Eye Dam. 1 - H318	
STOT SE 3 - H335	
Aquatic Acute 1 - H400	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Consult a physician for specific advice. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention immediately.
Ingestion	Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Do not induce vomiting unless under the direction of medical personnel. Get medical attention immediately.

JAM3500 (WB) Cleaner

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing. Wash clothing and clean shoes thoroughly before reuse.

Eye contact Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention.

Protection of first aiders First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information See Section 11 for additional information on health hazards.

Inhalation May cause respiratory system irritation. Vapours may cause drowsiness and dizziness.

Ingestion Harmful if swallowed. May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication.

Skin contact May cause irritation. Prolonged or repeated contact with skin may cause irritation, redness and dermatitis.

Eye contact This product is strongly irritating. Vapour or spray may cause temporary (reversible) eye damage. Symptoms following overexposure may include the following: Severe irritation, burning, tearing and blurred vision.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media Water spray.

5.2. Special hazards arising from the substance or mixture

Specific hazards Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO₂). Carbon monoxide (CO). Nitrous gases (NO_x).

5.3. Advice for firefighters

Protective actions during firefighting Evacuate area. Stop leak if safe to do so. Use water to keep fire exposed containers cool and disperse vapours. Use water spray to reduce vapours.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions No smoking, sparks, flames or other sources of ignition near spillage. Avoid contact with skin, eyes and clothing. Avoid inhalation of vapours. Wash thoroughly after dealing with a spillage.

6.2. Environmental precautions

Environmental precautions Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

JAM3500 (WB) Cleaner

Methods for cleaning up Eliminate all sources of ignition. Stop leak if safe to do so. Contain and absorb spillage with sand, earth or other non-combustible material. Dilute contained spill with water. Collect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product. Provide eyewash station and safety shower. Good personal hygiene procedures should be implemented. Wash skin thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep only in the original container in a cool, well-ventilated place.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Isopropanol

Long-term exposure limit (8-hour TWA): WEL 200 ppm 500 mg/m³ Austria, Belgium, Finland, Germany (AGS), Germany (DFG), Spain, Switzerland

Long-term exposure limit (8-hour TWA): WEL 200 ppm 490 mg/m³ Denmark

Long-term exposure limit (8-hour TWA): WEL 500 mg/m³ Hungary

Long-term exposure limit (8-hour TWA): WEL 200 ppm Ireland

Long-term exposure limit (8-hour TWA): WEL 350 mg/m³ Latvia

Long-term exposure limit (8-hour TWA): WEL 900 mg/m³ Poland

Long-term exposure limit (8-hour TWA): WEL 150 ppm 350 mg/m³ Sweden

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³ United Kingdom

Short-term exposure limit (15-minute): WEL 800 ppm 2000 mg/m³ Austria

Short-term exposure limit (15-minute): WEL 400 ppm 1000 mg/m³ Belgium, Germany (AGS), Germany (DFG), Spain, Switzerland

Short-term exposure limit (15-minute): WEL 400 ppm 980 mg/m³ Denmark, France

Short-term exposure limit (15-minute): WEL 250 ppm 620 mg/m³ Finland, Sweden

Short-term exposure limit (15-minute): WEL 2000 mg/m³ Hungary

Short-term exposure limit (15-minute): WEL 400 ppm Ireland

Short-term exposure limit (15-minute): WEL 600 mg/m³ Latvia

Short-term exposure limit (15-minute): WEL 1200 mg/m³ Poland

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³ United Kingdom

WEL = Workplace Exposure Limit

8.2. Exposure controls

JAM3500 (WB) Cleaner

Protective equipment



Appropriate engineering controls

As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist. Use explosion-proof ventilating equipment.

Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield.

Hand protection

It is recommended that chemical-resistant, impervious gloves are worn. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. It is recommended that gloves are made of the following material: Butyl rubber. Nitrile rubber. Rubber (natural, latex). Frequent changes are recommended.

Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measures

Provide eyewash station and safety shower.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Organic vapour filter.

Thermal hazards

If there is a risk of contact with hot product, all protective equipment worn should be suitable for use with high temperatures.

Environmental exposure controls

Keep container tightly sealed when not in use. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Coloured liquid.
Colour	Clear. Colourless. Water-white.
Odour	Alcoholic. Ammonia.
Odour threshold	Not available.
pH	pH (concentrated solution): 6.0 - 8.5
Melting point	0°C/32°F
Initial boiling point and range	100°C/212°F @ 760 mm Hg
Flash point	Not relevant.
Evaporation rate	3.0 (butyl acetate = 1)
Upper/lower flammability or explosive limits	Upper flammable/explosive limit: 16 % vol Lower flammable/explosive limit: 2.0 % vol
Vapour pressure	115 mm Hg @ 20°C/68°F
Vapour density	2.1
Relative density	0.971 g/cc 971 g/l 8.09 lbs/gal
Solubility(ies)	Soluble in the following materials: Alcohols. Completely soluble in water.

JAM3500 (WB) Cleaner

Partition coefficient	log Pow: 0.05
Auto-ignition temperature	425°C/797°F
Decomposition Temperature	Not applicable.
Explosive properties	Not applicable.
Oxidising properties	Not applicable.
Comments	Data based on literature. Product not tested. Information given is applicable to the product as supplied. Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures.

9.2. Other information

Volatile organic compound	This product contains a maximum VOC content of 97 g/l. This product contains a maximum VOC content of 0.81 lbs/gal.
----------------------------------	---

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
-------------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
------------------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	The following materials may react with the product: Strong oxidising agents.
---	--

10.4. Conditions to avoid

Conditions to avoid	Avoid the following conditions: Heat, sparks, flames. Freezing.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	Avoid contact with the following materials: Strong oxidising agents.
---------------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	Heating may generate the following products: Carbon dioxide (CO ₂). Carbon monoxide (CO). Nitrous gases (NO _x).
---	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects	Data based on literature. Product not tested.
------------------------------	---

Acute toxicity - oral

ATE oral (mg/kg)	25,000.0
-------------------------	----------

Specific target organ toxicity - single exposure

Target organs	Central nervous system Eyes
----------------------	-----------------------------

Specific target organ toxicity - repeated exposure

Target organs	Blood Central nervous system Gastro-intestinal tract Kidneys Liver Skin
----------------------	---

Aspiration hazard

Aspiration hazard	Not relevant.
--------------------------	---------------

Toxicological information on ingredients.

JAM3500 (WB) Cleaner

Isopropanol

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,045.0

Species Rat

ATE oral (mg/kg) 5,045.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 12,800.0

Species Rabbit

ATE dermal (mg/kg) 12,800.0

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

Ammonium hydroxide

Acute toxicity - oral

ATE oral (mg/kg) 500.0

SECTION 12: Ecological Information

Ecotoxicity Data based on literature. Product not tested.

12.1. Toxicity

Ecological information on ingredients.

Isopropanol

Acute toxicity - fish LC₅₀, 96 hours: 9640 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic invertebrates EC₅₀, 24 hours: 5102 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: > 2000 mg/l, Desmodemus subspicatus
EC₅₀, 24 hours: > 1000 mg/l, Algae

Ammonium hydroxide

Acute aquatic toxicity

LE(C)₅₀ 0.1 < L(E)C50 ≤ 1

M factor (Acute) 1

12.2. Persistence and degradability

12.3. Bioaccumulative potential

Partition coefficient log Pow: 0.05

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

JAM3500 (WB) Cleaner

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information

Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.

Disposal methods

Dispose of contents/container in accordance with national regulations. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. When handling waste, the safety precautions applying to handling of the product should be considered.

SECTION 14: Transport information

General

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

Inventories

EU - EINECS/ELINCS

All the ingredients are listed or exempt.

Canada - DSL/NDSL

JAM3500 (WB) Cleaner

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

Australia - AICS

The following ingredients are listed or exempt:

Isopropanol

Japan - MITI

The following ingredients are listed or exempt:

Isopropanol

Korea - KECI

The following ingredients are listed or exempt:

Isopropanol

China - IECSC

The following ingredients are listed or exempt:

Isopropanol

Philippines – PICCS

The following ingredients are listed or exempt:

Isopropanol

SECTION 16: Other information

General information	Containers of this material may be hazardous when emptied, all hazard precautions given in the data sheet must be observed.
Issued by	Matthews Marking Systems - Chemical Services Department
Revision date	31/12/2015
Revision	2
Supersedes date	01/06/2015
SDS number	5361
SDS status	Approved.
Risk phrases in full	R11 Highly flammable. R34 Causes burns. R36 Irritating to eyes. R36/38 Irritating to eyes and skin. R50 Very toxic to aquatic organisms. R67 Vapours may cause drowsiness and dizziness.
Hazard statements in full	H225 Highly flammable liquid and vapour. H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H318 Causes serious eye damage. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life.

JAM3500 (WB) Cleaner

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.