



SAFETY DATA SHEET JAM3704 Green (WB) Ink

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name JAM3704 Green (WB) Ink
Product number 71001840
Container size 55 Gallon Drum

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Printing ink.
Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Matthews Marking Systems
 6515 Penn Avenue
 Pittsburgh, PA 15206
 412.665.2500
 412.828.4545
 info@matw.com

Manufacturer Matthews Marking Systems
 101 Fairview Ave.
 Pittsburgh, PA 15238

1.4. Emergency telephone number

Emergency telephone Chemtrec US : 1-800-424-9300 Chemtrec World: 1-703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified
Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Repr. 1B - H360D STOT SE 3 - H335
Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) Xi; R41, R37/38. Repr. Cat. 1 R61. R43

2.2. Label elements

Pictogram



Signal word

Danger

JAM3704 Green (WB) Ink

Hazard statements	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H335 May cause respiratory irritation. H360D May damage the unborn child.
Comments	Full list of Hazard Statements is found in Sec. 16
Precautionary statements	P261 Avoid breathing vapour/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/attention. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P501 Dispose of contents/container in accordance with national regulations.
Contains	Mpyrol, N-Propanol, Proprietary - Dye - Yellow
Supplementary precautionary statements	P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P310 Immediately call a POISON CENTER/doctor. P312 Call a POISON CENTER/doctor if you feel unwell. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/attention. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P405 Store locked up.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Mpyrol	10-30%
CAS number: 872-50-4	EC number: 212-828-1
Classification	Classification (67/548/EEC or 1999/45/EC)
Skin Irrit. 2 - H315	Xi; R36/37/38. Repr. Cat. 1 R61
Eye Irrit. 2 - H319	
Repr. 1B - H360D	
STOT SE 3 - H335	
N-Propanol	10-30%
CAS number: 71-23-8	EC number: 200-746-9
Classification	
Flam. Liq. 2 - H225	
Eye Dam. 1 - H318	
STOT SE 3 - H336	

JAM3704 Green (WB) Ink

Proprietary - Dye - Yellow		1-5%
CAS number: Proprietary	EC number: Proprietary	REACH registration number: Proprietary
Classification		
Eye Irrit. 2 - H319		
Skin Sens. 1B - H317		

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Consult a physician for specific advice. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention immediately.
Ingestion	Get medical attention immediately. Do not induce vomiting. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Rinse cautiously with water for several minutes. Get medical attention promptly if symptoms occur after washing. Wash clothing and clean shoes thoroughly before reuse.
Eye contact	Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

4.2. Most important symptoms and effects, both acute and delayed

General information	See Section 11 for additional information on health hazards.
Inhalation	Gas or vapour in high concentrations may irritate the respiratory system. Overexposure may depress the central nervous system, causing dizziness and intoxication.
Ingestion	This product is moderately irritating. May cause nausea, headache, dizziness and intoxication.
Skin contact	Causes skin irritation. Symptoms following overexposure may include the following: Irritation. Redness. Mild dermatitis, allergic skin rash.
Eye contact	Causes serious eye irritation. Symptoms following overexposure may include the following: Pain. Severe irritation, burning, tearing and blurred vision.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	None known.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.
-------------------------	--

JAM3704 Green (WB) Ink

Hazardous combustion products Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO₂). Carbon monoxide (CO).

5.3. Advice for firefighters

Protective actions during firefighting Evacuate area. Stop leak if safe to do so. Use water to keep fire exposed containers cool and disperse vapours. Use water spray to reduce vapours.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions No smoking, sparks, flames or other sources of ignition near spillage. Avoid contact with skin, eyes and clothing. Avoid inhalation of vapours. Wash thoroughly after dealing with a spillage.

6.2. Environmental precautions

Environmental precautions Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. Stop leak if safe to do so. Contain and absorb spillage with sand, earth or other non-combustible material. Dilute contained spill with water. Collect and place in suitable waste disposal containers and seal securely.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Advice on general occupational hygiene Do not eat, drink or smoke when using this product. Provide eyewash station and safety shower. Good personal hygiene procedures should be implemented. Wash skin thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep only in the original container in a cool, well-ventilated place.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Mpyrol

JAM3704 Green (WB) Ink

Long-term exposure limit (8-hour TWA): WEL 10 ppm 40 mg/m³ Austria, Belgium, European Union, Finland, France, Ireland, Italy

Long-term exposure limit (8-hour TWA): WEL 5 ppm 20 mg/m³ Denmark

Long-term exposure limit (8-hour TWA): WEL 20 ppm 82 mg/m³ Germany (AGS), Germany (DFG)

Long-term exposure limit (8-hour TWA): WEL 100 mg/m³ Latvia

Long-term exposure limit (8-hour TWA): WEL 40 mg/m³ Poland, The Netherlands

Long-term exposure limit (8-hour TWA): WEL 25 ppm 103 mg/m³ Spain, United Kingdom

Long-term exposure limit (8-hour TWA): WEL 50 ppm 200 mg/m³ Sweden

Long-term exposure limit (8-hour TWA): WEL 20 ppm 80 mg/m³ Switzerland

Short-term exposure limit (15-minute): WEL 20 ppm 80 mg/m³ Austria, Belgium, European Union, Finland, France, Ireland, Italy

Short-term exposure limit (15-minute): WEL 10 ppm 40 mg/m³ Denmark

Short-term exposure limit (15-minute): WEL 40 ppm 164 mg/m³ Germany (AGS), Germany (DFG)

Short-term exposure limit (15-minute): WEL 80 mg/m³ Poland, The Netherlands

Short-term exposure limit (15-minute): WEL 75 ppm 309 mg/m³ Spain, United Kingdom

Short-term exposure limit (15-minute): WEL 75 ppm 300 mg/m³ Sweden

Short-term exposure limit (15-minute): WEL 40 ppm 160 mg/m³ Switzerland

Sk

N-Propanol

Long-term exposure limit (8-hour TWA): WEL 200 ppm 500 mg/m³ Austria, Denmark, Finland, France, Spain, Switzerland, United Kingdom

Long-term exposure limit (8-hour TWA): WEL 100 ppm 250 mg/m³ Belgium

Long-term exposure limit (8-hour TWA): WEL 10 ppm Ireland

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ Latvia

Long-term exposure limit (8-hour TWA): WEL 200 mg/m³ Poland

Long-term exposure limit (8-hour TWA): WEL 150 ppm 350 mg/m³ Sweden

Short-term exposure limit (15-minute): WEL 400 ppm 1000 mg/m³ Denmark, Spain

Short-term exposure limit (15-minute): WEL 250 ppm 620 mg/m³ Finland

Short-term exposure limit (15-minute): WEL 600 mg/m³ Poland

Short-term exposure limit (15-minute): WEL 250 ppm 600 mg/m³ Sweden

Short-term exposure limit (15-minute): WEL 250 ppm 625 mg/m³ United Kingdom

Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist. Use explosion-proof ventilating equipment.

Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield.

Hand protection

It is recommended that chemical-resistant, impervious gloves are worn. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. It is recommended that gloves are made of the following material: Butyl rubber. Nitrile rubber. Rubber (natural, latex). Frequent changes are recommended.

JAM3704 Green (WB) Ink

Other skin and body protection	Wear appropriate clothing to prevent repeated or prolonged skin contact.
Hygiene measures	Provide eyewash station and safety shower.
Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Organic vapour filter.
Thermal hazards	If there is a risk of contact with hot product, all protective equipment worn should be suitable for use with high temperatures.
Environmental exposure controls	Keep container tightly sealed when not in use. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Coloured liquid.
Colour	Green.
Odour	Alcoholic.
Odour threshold	Not available.
pH	pH (concentrated solution): 6.0 - 8.5
Melting point	0°C/32°F
Initial boiling point and range	97°C/207°F @ 760 mm Hg
Flash point	Not relevant.
Evaporation rate	0.89 (butyl acetate = 1)
Upper/lower flammability or explosive limits	Upper flammable/explosive limit: 14 % vol Lower flammable/explosive limit: 1.3 % vol
Vapour pressure	14.5 mm Hg @ 20°C/68°F
Vapour density	3.42
Relative density	0.986 g/cm ³ 986 g/l 8.21 lbx/gal
Solubility(ies)	Soluble in the following materials: Alcohols. Soluble in water.
Partition coefficient	log Pow: 0.05
Auto-ignition temperature	413°C/775.4°F
Decomposition Temperature	Not applicable.
Explosive properties	Not applicable.
Oxidising properties	Not applicable.
Comments	Data based on literature. Product not tested. Information given is applicable to the product as supplied. Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures.

9.2. Other information

Volatile organic compound	This product contains a maximum VOC content of 320 g/l. This product contains a maximum VOC content of 2.67 lbs/gal.
----------------------------------	--

SECTION 10: Stability and reactivity

JAM3704 Green (WB) Ink

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions The following materials may react with the product: Strong acids. Strong oxidising agents. Strong reducing agents.

10.4. Conditions to avoid

Conditions to avoid Avoid the following conditions: Heat, sparks, flames. Freezing.

10.5. Incompatible materials

Materials to avoid Avoid contact with the following materials: Strong acids. Strong oxidising agents. Strong reducing agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Heating may generate the following products: Carbon dioxide (CO₂). Carbon monoxide (CO).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects Data based on literature. Product not tested.

Specific target organ toxicity - single exposure

Target organs Central nervous system Eyes Gastro-intestinal tract Respiratory system, lungs Skin

Specific target organ toxicity - repeated exposure

Target organs Skin

Aspiration hazard

Aspiration hazard Not anticipated to present an aspiration hazard, based on chemical structure.

Toxicological information on ingredients.

Mpyrol

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 3,914.0

Species Rat

ATE oral (mg/kg) 3,914.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 8,000.0

Species Rabbit

ATE dermal (mg/kg) 8,000.0

Carcinogenicity

JAM3704 Green (WB) Ink

IARC carcinogenicity	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen
NTP carcinogenicity	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen

N-Propanol

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ 3830 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ > 10,000 mg/kg, Dermal, Rabbit

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LD₅₀ > 9.8 mg/l, Inhalation, Rat

Skin corrosion/irritation

Animal data Slightly irritating.

SECTION 12: Ecological Information

Ecotoxicity Data based on literature. Product not tested.

Ecological information on ingredients.

Mpyrol

Ecotoxicity Dangerous for the environment.

12.1. Toxicity

Ecological information on ingredients.

Mpyrol

Acute toxicity - fish LC₅₀, 96 hours: 4000 mg/l, Fish
LC₅₀, 96 hours: >500 mg/l, Leuciscus idus (Golden orfe)

Acute toxicity - aquatic invertebrates EC₅₀, 24 hours: >1000 mg/l, Daphnia magna

N-Propanol

Acute toxicity - fish LC₅₀, 96 hours: > 804 mg/l, Pimephales promelas (Fat-head Minnow)

Acute toxicity - aquatic invertebrates LC₅₀, 96 hours: > 804 mg/l, Daphnia magna

12.2. Persistence and degradability

12.3. Bioaccumulative potential

Partition coefficient log Pow: 0.05

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

JAM3704 Green (WB) Ink

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information

Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.

Disposal methods

Dispose of contents/container in accordance with national regulations. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. When handling waste, the safety precautions applying to handling of the product should be considered.

SECTION 14: Transport information

General

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

15.2. Chemical safety assessment

Inventories

EU - EINECS/ELINCS

All the ingredients are listed or exempt.

JAM3704 Green (WB) Ink

Canada - DSL/NDSL

All the ingredients are listed or exempt.

US - TSCA

All the ingredients are listed or exempt.

Australia - AICS

The following ingredients are listed or exempt:

N-Propanol

Japan - MITI

The following ingredients are listed or exempt:

N-Propanol

Korea - KECI

The following ingredients are listed or exempt:

N-Propanol

China - IECSC

The following ingredients are listed or exempt:

N-Propanol

Philippines – PICCS

The following ingredients are listed or exempt:

N-Propanol

SECTION 16: Other information

General information	Containers of this material may be hazardous when emptied, all hazard precautions given in the data sheet must be observed.
Issued by	Matthews Marking Systems - Chemical Services Department
Revision date	31/12/2015
Revision	2
Supersedes date	01/06/2015
SDS number	5482
SDS status	Approved.
Risk phrases in full	R11 Highly flammable. R36/37/38 Irritating to eyes, respiratory system and skin. R37/38 Irritating to respiratory system and skin. R41 Risk of serious damage to eyes. R43 May cause sensitisation by skin contact. R61 May cause harm to the unborn child. R67 Vapours may cause drowsiness and dizziness.

JAM3704 Green (WB) Ink

Hazard statements in full

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H360D May damage the unborn child.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.