

## Product Name: L-218 Red Ink

---

### Substrates Marked

**Preferred:** Metals, Fabrics, Paper and some Plastics  
**Acceptable:** Various porous and non-porous substrates

### Product Specifications/Characteristics

<b>UN Number</b>	1210	<b>Flash Point</b>	16° F (-9°C)
<b>Type</b>	CIJ	<b>Recommended Storage</b>	32°- 90° F (0°C – 32.2°C)
<b>Colorant</b>	Dye	<b>Shelf Life</b>	2 years
<b>Viscosity</b>	Liquid	<b>Package</b>	Vapor barrier polyethylene
<b>Drying Time</b>	<5 seconds	<b>Unit</b>	½ Liter Bottle
<b>Open Time</b>	N/A	<b>Density</b>	7.22 lbs/gal
<b>DOT Regulations</b>	Flammable	<b>RCRA Waste Number</b>	D001, D035, F005
<b>VOC</b>	738 g/l	<b>Thinner</b>	L-9219 Make-up Solution
<b>SDS Sheet Number</b>	5502	<b>Cleaner</b>	L-200
<b>HMS Rating</b>	1*-3-0	<b>NFPA Rating</b>	1-3-0
<b>Carcinogen</b>	No	<b>Specific Gravity</b>	0.866

### Description/Special Properties

This ink is ketone based and poses good adhesion and abrasion properties on a range of substrates from paper/boards through metals and many plastics with very fast drying times (<5 seconds).

### Application/Compatibility

**Printhead:** C84  
**Rubber Compounds:** N/A

### Formulations Available

Item Number	Unit of Measure
710015274	Case of 6 x ½ Liter Bottles

A Safety Data Sheet is furnished with every order.

**Original Date:** June 21, 2016

**Revision Date:**

---