



## SAFETY DATA SHEET

### M119 Red Offset Ink

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product name M119 Red Offset Ink  
 Product number 71000837  
 Container size 6 x 1 Liter

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Printing ink.  
 Uses advised against No specific uses advised against are identified.

##### 1.3. Details of the supplier of the safety data sheet

Supplier Matthews Marking Systems  
 6515 Penn Avenue  
 Pittsburgh, PA 15206  
 412.665.2500  
 412.828.4545  
 info@matw.com

Manufacturer Matthews Marking Systems  
 101 Fairview Ave.  
 Pittsburgh, PA 15238

##### 1.4. Emergency telephone number

Emergency telephone Chemtrec US : 1-800-424-9300 Chemtrec World: 1-703-527-3887

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification

Physical hazards Not Classified  
 Health hazards Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319  
 Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) Xn; R22. Xi; R36/38

##### 2.2. Label elements

###### Pictogram



Signal word Warning

## M119 Red Offset Ink

<b>Hazard statements</b>	H302 Harmful if swallowed. H315 Causes skin irritation. H319 Causes serious eye irritation.
<b>Comments</b>	Full list of Hazard Statements is found in Sec. 16
<b>Precautionary statements</b>	P264 Wash contaminated skin thoroughly after handling. P280 Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention. P501 Dispose of contents/container in accordance with national regulations.
<b>Contains</b>	Glycol Ether EB
<b>Supplementary precautionary statements</b>	P270 Do not eat, drink or smoke when using this product. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor. P302+P352 IF ON SKIN: Wash with plenty of water. P321 Specific treatment (see medical advice on this label). P330 Rinse mouth. P362+P364 Take off contaminated clothing and wash it before reuse.

### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

<b>Glycol Ether EB</b>	<b>10-30%</b>
CAS number: 111-76-2	EC number: 203-905-0
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Acute Tox. 4 - H302	Xn; R22. Xi; R36/38
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
<b>Glycol Ether DB</b>	<b>10-30%</b>
CAS number: 112-34-5	EC number: 203-961-6
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>
Skin Irrit. 2 - H315	Xi; R36/37/38
Eye Irrit. 2 - H319	
STOT SE 3 - H335	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

#### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

**General information** Consult a physician for specific advice. Show this Safety Data Sheet to the medical personnel.

## M119 Red Offset Ink

<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. If breathing stops, provide artificial respiration. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention immediately.
<b>Ingestion</b>	Get medical attention immediately. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Do not induce vomiting unless under the direction of medical personnel.
<b>Skin contact</b>	Rinse immediately contaminated clothing and skin with plenty of water before removing clothes. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing. Wash clothing and clean shoes thoroughly before reuse.
<b>Eye contact</b>	Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	See Section 11 for additional information on health hazards.
<b>Inhalation</b>	Gas or vapour in high concentrations may irritate the respiratory system. Vapour may affect central nervous system. Vapours may cause headache, fatigue, dizziness and nausea.
<b>Ingestion</b>	May be harmful if swallowed. May cause nausea, headache, dizziness and intoxication.
<b>Skin contact</b>	Prolonged or repeated contact with skin may cause irritation, redness and dermatitis.
<b>Eye contact</b>	May cause irritation. A single exposure may cause the following adverse effects: Pain. Severe irritation, burning, tearing and blurred vision. Corneal damage.

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Treat symptomatically.
-----------------------------	------------------------

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
<b>Unsuitable extinguishing media</b>	None known.

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards</b>	Combustible liquid. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.
<b>Hazardous combustion products</b>	Thermal decomposition or combustion products may include the following substances: Carbon dioxide (CO <sub>2</sub> ). Carbon monoxide (CO).

### 5.3. Advice for firefighters

<b>Protective actions during firefighting</b>	Evacuate area. Stop leak if safe to do so. Use water to keep fire exposed containers cool and disperse vapours. Use water spray to reduce vapours.
<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

## M119 Red Offset Ink

**Personal precautions** No smoking, sparks, flames or other sources of ignition near spillage. Avoid contact with skin, eyes and clothing. Avoid inhalation of vapours. Wash thoroughly after dealing with a spillage.

### 6.2. Environmental precautions

**Environmental precautions** Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Eliminate all sources of ignition. Stop leak if safe to do so. Contain and absorb spillage with sand, earth or other non-combustible material. Dilute contained spill with water. Collect and place in suitable waste disposal containers and seal securely.

### 6.4. Reference to other sections

**Reference to other sections** For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Wear protective clothing as described in Section 8 of this safety data sheet.

**Advice on general occupational hygiene** Do not eat, drink or smoke when using this product. Provide eyewash station and safety shower. Good personal hygiene procedures should be implemented. Wash skin thoroughly after handling.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Keep only in the original container in a cool, well-ventilated place.

**Storage class** Flammable liquid storage.

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### Glycol Ether EB

Long-term exposure limit (8-hour TWA): WEL 20 ppm 98 mg/m<sup>3</sup> Austria, Belgium, Denmark, European Union, Finland, Ireland, Italy, Latvia, Spain

Long-term exposure limit (8-hour TWA): WEL 25 ppm 123 mg/m<sup>3</sup> United Kingdom

Long-term exposure limit (8-hour TWA): WEL 10 ppm 49 mg/m<sup>3</sup> France, Germany (AGS), Germany (DFG), Switzerland

Long-term exposure limit (8-hour TWA): WEL 98 mg/m<sup>3</sup> Hungary, Poland

Long-term exposure limit (8-hour TWA): WEL 10 ppm 50 mg/m<sup>3</sup> Sweden

Long-term exposure limit (8-hour TWA): WEL 100 mg/m<sup>3</sup> The Netherlands

Short-term exposure limit (15-minute): WEL 40 ppm 200 mg/m<sup>3</sup> Austria

Short-term exposure limit (15-minute): WEL 50 ppm 246 mg/m<sup>3</sup> Belgium, European Union, France, Ireland, Italy, Latvia, United Kingdom

Short-term exposure limit (15-minute): WEL 40 ppm 196 mg/m<sup>3</sup> Denmark, Germany (AGS)

Short-term exposure limit (15-minute): WEL 50 ppm 250 mg/m<sup>3</sup> Finland

Short-term exposure limit (15-minute): WEL 20 ppm 98 mg/m<sup>3</sup> Germany (DFG), Switzerland

Short-term exposure limit (15-minute): WEL 246 mg/m<sup>3</sup> Hungary, The Netherlands

Short-term exposure limit (15-minute): WEL 200 mg/m<sup>3</sup> Poland

Short-term exposure limit (15-minute): WEL 50 ppm 245 mg/m<sup>3</sup> Spain

Short-term exposure limit (15-minute): WEL 20 ppm 100 mg/m<sup>3</sup> Sweden

Sk

## M119 Red Offset Ink

### Glycol Ether DB

Long-term exposure limit (8-hour TWA): WEL 10 ppm 67.5 mg/m<sup>3</sup> Austria, Belgium, European Union, France, Ireland, Italy, Latvia, Spain, United Kingdom

Long-term exposure limit (8-hour TWA): WEL 100 mg/m<sup>3</sup> Denmark

Long-term exposure limit (8-hour TWA): WEL 10 ppm 68 mg/m<sup>3</sup> Finland

Long-term exposure limit (8-hour TWA): WEL 10 ppm 67 mg/m<sup>3</sup> Germany (AGS), Germany (DFG), Switzerland

Long-term exposure limit (8-hour TWA): WEL 67.5 mg/m<sup>3</sup> Hungary

Long-term exposure limit (8-hour TWA): WEL 67 mg/m<sup>3</sup> Poland

Long-term exposure limit (8-hour TWA): WEL 15 ppm 100 mg/m<sup>3</sup> Sweden

Long-term exposure limit (8-hour TWA): WEL 50 mg/m<sup>3</sup> The Netherlands

Short-term exposure limit (15-minute): WEL 15 ppm 101.2 mg/m<sup>3</sup> Austria, Belgium, European Union, France, Ireland, Italy, Latvia, Spain, Switzerland, United Kingdom

Short-term exposure limit (15-minute): WEL 15 ppm 100 mg/m<sup>3</sup> Germany (AGS)

Short-term exposure limit (15-minute): WEL 15 ppm 100.5 mg/m<sup>3</sup> Germany (DFG)

Short-term exposure limit (15-minute): WEL 101.2 mg/m<sup>3</sup> Hungary

Short-term exposure limit (15-minute): WEL 100 mg/m<sup>3</sup> Poland, The Netherlands

Short-term exposure limit (15-minute): WEL 30 ppm 200 mg/m<sup>3</sup> Sweden

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapour or mist. Use explosion-proof ventilating equipment.

#### Eye/face protection

Wear tight-fitting, chemical splash goggles or face shield.

#### Hand protection

It is recommended that chemical-resistant, impervious gloves are worn. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. It is recommended that gloves are made of the following material: Butyl rubber. Nitrile rubber. Rubber (natural, latex). Frequent changes are recommended.

#### Other skin and body protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

#### Hygiene measures

Provide eyewash station and safety shower.

#### Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Wear a respirator fitted with the following cartridge: Organic vapour filter.

#### Thermal hazards

If there is a risk of contact with hot product, all protective equipment worn should be suitable for use with high temperatures.

#### Environmental exposure controls

Keep container tightly sealed when not in use. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

**Appearance** Coloured liquid.

## M119 Red Offset Ink

<b>Colour</b>	Red.
<b>Odour</b>	Ether.
<b>Odour threshold</b>	Not available.
<b>pH</b>	pH (concentrated solution): 6.0 - 8.5
<b>Melting point</b>	-75°C/-103°F
<b>Initial boiling point and range</b>	169°C/336°F @ 760 mm Hg
<b>Flash point</b>	67°C/153°F CC (Closed cup).
<b>Evaporation rate</b>	0.1 (butyl acetate = 1)
<b>Upper/lower flammability or explosive limits</b>	Upper flammable/explosive limit: 12.7 % vol Lower flammable/explosive limit: 0.95 % vol
<b>Vapour pressure</b>	0.6 mm Hg @ 20°C/68°F
<b>Vapour density</b>	4.08
<b>Relative density</b>	1.070 g/cm <sup>3</sup> 1070 g/l 8.92 lbs/gal
<b>Solubility(ies)</b>	Soluble in the following materials: Ether. Miscible with water.
<b>Partition coefficient</b>	log Pow: 0.83
<b>Auto-ignition temperature</b>	204°C/400°F
<b>Decomposition Temperature</b>	Not applicable.
<b>Explosive properties</b>	Not applicable.
<b>Oxidising properties</b>	Not applicable.
<b>Comments</b>	Data based on literature. Product not tested. Information given is applicable to the product as supplied. Information declared as "Not available" or "Not applicable" is not considered to be relevant to the implementation of the proper control measures.

### 9.2. Other information

<b>Volatile organic compound</b>	This product contains a maximum VOC content of 493 g/l. This product contains a maximum VOC content of 4.11 lbs/gal.
----------------------------------	--

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

<b>Reactivity</b>	There are no known reactivity hazards associated with this product.
-------------------	---

### 10.2. Chemical stability

<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended.
------------------	---

### 10.3. Possibility of hazardous reactions

<b>Possibility of hazardous reactions</b>	The following materials may react with the product: Strong oxidising agents.
---	--

### 10.4. Conditions to avoid

<b>Conditions to avoid</b>	Avoid the following conditions: Heat, sparks, flames.
----------------------------	---

### 10.5. Incompatible materials

<b>Materials to avoid</b>	Avoid contact with the following materials: Strong oxidising agents.
---------------------------	--

## M119 Red Offset Ink

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Heating may generate the following products: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide (CO).

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

**Toxicological effects** Data based on literature. Product not tested.

##### Acute toxicity - oral

**ATE oral (mg/kg)** 1,883.95

##### Acute toxicity - dermal

**ATE dermal (mg/kg)** 4,144.69

##### Acute toxicity - inhalation

**ATE inhalation (vapours mg/l)** 41.45

##### Specific target organ toxicity - single exposure

**Target organs** Central nervous system Eyes Gastro-intestinal tract Respiratory system, lungs Skin

##### Specific target organ toxicity - repeated exposure

**Target organs** Central nervous system Eyes Gastro-intestinal tract Respiratory system, lungs Skin

##### Aspiration hazard

**Aspiration hazard** Not relevant.

##### Toxicological information on ingredients.

#### Glycol Ether EB

##### Acute toxicity - oral

**ATE oral (mg/kg)** 500.0

##### Acute toxicity - dermal

**ATE dermal (mg/kg)** 1,100.0

##### Acute toxicity - inhalation

**ATE inhalation (vapours mg/l)** 11.0

##### Carcinogenicity

**IARC carcinogenicity** IARC Group 3 Not classifiable as to its carcinogenicity to humans.

### SECTION 12: Ecological Information

**Ecotoxicity** Data based on literature. Product not tested.

#### 12.1. Toxicity

##### Ecological information on ingredients.

#### Glycol Ether EB

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: 220 mg/l, Fish

#### 12.2. Persistence and degradability

#### 12.3. Bioaccumulative potential

## M119 Red Offset Ink

**Partition coefficient** log Pow: 0.83

### 12.4. Mobility in soil

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### **General information**

Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements.

#### **Disposal methods**

Dispose of contents/container in accordance with national regulations. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. When handling waste, the safety precautions applying to handling of the product should be considered.

## SECTION 14: Transport information

#### **General**

The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

#### 14.1. UN number

Not applicable.

#### 14.2. UN proper shipping name

Not applicable.

#### 14.3. Transport hazard class(es)

No transport warning sign required.

#### 14.4. Packing group

Not applicable.

#### 14.5. Environmental hazards

##### **Environmentally hazardous substance/marine pollutant**

No.

#### 14.6. Special precautions for user

Not applicable.

#### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

**Annex II of MARPOL 73/78  
and the IBC Code**

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU legislation**

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

### 15.2. Chemical safety assessment



## M119 Red Offset Ink

### Inventories

#### **EU - EINECS/ELINCS**

All the ingredients are listed or exempt.

#### **Canada - DSL/NDSL**

All the ingredients are listed or exempt.

#### **US - TSCA**

All the ingredients are listed or exempt.

#### **Australia - AICS**

The following ingredients are listed or exempt:

**Glycol Ether EB**

**Glycol Ether DB**

#### **Japan - MITI**

The following ingredients are listed or exempt:

**Glycol Ether EB**

**Glycol Ether DB**

#### **Korea - KECI**

The following ingredients are listed or exempt:

**Glycol Ether EB**

**Glycol Ether DB**

#### **China - IECSC**

The following ingredients are listed or exempt:

**Glycol Ether EB**

**Glycol Ether DB**

#### **Philippines – PICCS**

The following ingredients are listed or exempt:

**Glycol Ether EB**

**Glycol Ether DB**

### **SECTION 16: Other information**

<b>General information</b>	Containers of this material may be hazardous when emptied, all hazard precautions given in the data sheet must be observed.
<b>Issued by</b>	Matthews Marking Systems - Chemical Services Department
<b>Revision date</b>	31/12/2015
<b>Revision</b>	2
<b>Supersedes date</b>	01/06/2015
<b>SDS number</b>	5559
<b>SDS status</b>	Approved.

## M119 Red Offset Ink

**Risk phrases in full**

R22 Harmful if swallowed.  
R36/37/38 Irritating to eyes, respiratory system and skin.  
R36/38 Irritating to eyes and skin.

**Hazard statements in full**

H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H335 May cause respiratory irritation.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.