

## Product Name: SCP-300A Black Ink

---

### Substrates Marked

**Preferred:** Corrugated board and paper  
**Acceptable:** Porous substrates

### Product Specifications/Characteristics

<b>UN Number</b>	N/A	<b>Flash Point</b>	>212° F (>100°C)
<b>Type</b>	Ink Jet	<b>Recommended Storage</b>	40°- 90° F (4.4°C – 32.2°C)
<b>Colorant</b>	Dye	<b>Shelf Life</b>	2 years
<b>Viscosity</b>	Liquid	<b>Package</b>	Vapor barrier polyethylene
<b>Drying Time</b>	1-5 seconds	<b>Unit</b>	Various
<b>Open Time</b>	N/A	<b>Density</b>	8.41 lbs/gal
<b>DOT Regulations</b>	N/A	<b>RCRA Waste Number</b>	N/A
<b>VOC</b>	0 g/l	<b>Thinner</b>	N/A
<b>SDS Sheet Number</b>	4884	<b>Cleaner</b>	JAM-3005 Cleaner
<b>HMIS Rating</b>	1*-0-0	<b>NFPA Rating</b>	1-0-0
<b>Carcinogen</b>	No	<b>Specific Gravity</b>	1.013

### Description/Special Properties

Water based ink for use on porous substrates. Dry times for this ink will depend on the porosity of the substrate. This ink will not ignite or support combustion. This ink has zero VOC's.

### Application/Compatibility

**Printhead:** 8000+  
**Rubber Compounds:** N/A

### Formulations Available

<b>Item Number</b>	<b>Unit of Measure</b>
71002391	Case of 6 x 1 Liter Bottles
71002392	Case of 6 x 1 Liter Bottles
71002393	Case of 6 x ½ Liter Bottles
71002387	Case of 2 x 4 Liter Bottles
71002389	5 Gallon Pail
71002388	55 Gallon Drum

A Safety Data Sheet is furnished with every order.

**Original Date:** March 14, 2013  
**Revision Date:** June 23, 2016

---