

Product Name: SCP-650 Black (FD) Ink

Substrates Marked

Preferred: Various porous and non-porous substrates
Acceptable: N/A

Product Specifications/Characteristics

UN Number	1210	Flash Point	53.6° F (12°C)
Type	Ink Jet	Recommended Storage	32°- 90° F (0°C – 32.2°C)
Colorant	Dye	Shelf Life	2 years
Viscosity	Liquid	Package	Vapor barrier polyethylene
Drying Time	10-30 seconds	Unit	Various
Open Time	N/A	Density	6.77 lbs/gal
DOT Regulations	Flammable	RCRA Waste Number	D001
VOC	760 g/l	Thinner	N/A
SDS Sheet Number	5316	Cleaner	SCP-620C Cleaner
HMS Rating	2*-3-0	NFPA Rating	2-3-0
Carcinogen	No	Specific Gravity	0.813

Description/Special Properties

Alcohol based ink formulated to be acceptable on both porous and non-porous applications. Dry times for this ink will be 10-30 seconds. This can be speeded up with the use of heated or forced air. This material is approved for FDA 21 CFR 170.39.

Application/Compatibility

Printhead: 8000+
Rubber Compounds: N/A

Formulations Available

Item Number	Unit of Measure
71002273	Case of 6 x 1 Liter Bottles
71002274	Case of 6 x 1 Liter Bottles
71002270	Case of 2 x 4 Liter Bottles
71002271	5 Gallon Pail

A Safety Data Sheet is furnished with every order.

Original Date: January 6, 2013
Revision Date: June 23, 2016
