# Product Name: SCP-671 DW Blue Ink

## Substrates Marked

Preferred:	Drywall, Gypsum Board
Acceptable:	Porous substrates

#### **Product Specifications/Characteristics**

UN Number	1210	Flash Point	24° F (-4°C)
Туре	Ink Jet	Recommended Storage	40°-90° F (4.4°C – 32.2°C)
Colorant	Dye	Shelf Life	2 years
Viscosity	Liquid	Package	Vapor barrier polyethylene
Drying Time	1-10 seconds	Unit	Various
Open Time	N/A	Density	6.79 lbs/gal
DOT Regulations	Flammable	RCRA Waste Number	D001
VOC	755 g/l	Thinner	N/A
SDS Sheet Number	4930	Cleaner	SCP-620C Cleaner
HMIS Rating	2*-3-0	NFPA Rating	2-3-0
Carcinogen	No	Specific Gravity	0.815

#### **Description/Special Properties**

Blue ethanol based ink to be used for printing on drywall, gypsum board and other porous substrates. This ink will have a higher dye content than the SCP-680 series. This ink will exhibit excellent drop formation and requires very little maintenance on the printhead. The ink can potentially be used on non-porous substrates but will be very light since it is characterized as a drywall ink. Sample marking should be done before it is recommended for non-porous applications.

### Application/Compatibility

Printhead: 8000+ Rubber Compounds: N/A

#### **Formulations Available**

Item Number	Unit of Measure
71062884	Case of 6 x 1 Liter Bottles
71076984	Case of 2 x 4 Liter Bottles
71013356	5 Gallon Pail

A Safety Data Sheet is furnished with every order.

Original Date: June 28, 2016 Revision Date:

