

Product Name: SCP-750 Black (FD) Ink

Substrates Marked

Preferred: Various porous and non-porous substrates

Acceptable: N/A

Product Specifications/Characteristics

| UN Number | 1210 | Flash Point | 16° F (-9°C) |
|------------------|-------------|---------------------|----------------------------|
| Туре | Ink Jet | Recommended Storage | 32°- 90° F (0°C – 32.2°C) |
| Colorant | Dye | Shelf Life | 2 years |
| Viscosity | Liquid | Package | Vapor barrier polyethylene |
| Drying Time | 1-5 seconds | Unit | Various |
| Open Time | N/A | Density | 7.09 lbs/gal |
| DOT Regulations | Flammable | RCRA Waste Number | D001, D035, F005 |
| VOC | 790 g/l | Thinner | N/A |
| SDS Sheet Number | 4836 | Cleaner | SCP-700C Cleaner |
| HMIS Rating | 2*-3-0 | NFPA Rating | 2-3-0 |
| Carcinogen | No | Specific Gravity | 0.851 |

Description/Special Properties

Fast dry ink formulated to be acceptable for use on substrates where incidental food contact may occur. This material is approved for FDA 21 CFR 170.39. Cannot be used for printing directly on the food surface itself. Used for both porous and non-porous applications. Dry times for this ink will be 1-5 seconds.

Application/Compatibility

Printhead: 8000+ Rubber Compounds: N/A

Formulations Available

| Item Number | Unit of Measure |
|-------------|-----------------------------|
| 71002278 | Case of 6 x 1 Liter Bottles |
| 71002279 | Case of 6 x 1 Liter Bottles |
| 71002275 | Case of 2 x 4 Liter Bottles |
| 71002276 | 5 Gallon Pail |

A Safety Data Sheet is furnished with every order.

Original Date: November 9, 2012 Revision Date: June 28, 2016

